

GVSP-15T SPEAKER

An efficient and weather-resistant solution for your warning system



The GVSP-15T environment-resistant loudspeaker is the world standard for high-intelligibility voice and signal transmission in medium-power indoor and outdoor public address, intercom, security and industrial-signal-system applications. Cost effective, 15-watt units incorporate high-efficiency compression drivers to project sound over long distances or wide areas with fewer loudspeakers.

FEATURES

- o Superior intelligibility for voice and tone signalling
- o High-efficiency driver with proven performance reliability
- o Transformer for versatile 25, 70.7 or 100 V line application
- o Brackets for precise positioning
- o Environment resistant for outdoor and indoor use

Output Data:

Power Rating:	15 watts continuous
Frequency Response:	400 – 14,000 Hz (Nominal) 500 Hz – 6,000 Hz (± 5dB)
Sensitivity:	120dB at 15 Watts (peak) 106dB 1 Watt/Meter (avg) 500 – 6000 Hz
Dispersion Angle:	70°

Dimensions

Width:	20 cm
Height:	22.2 cm
Depth:	23.7 cm
Weight:	1.8 kg

Impedance switch setting

The GVSP-15T has a built-in 7 position switch. The weather-sealed switch selects impedance or wattage taps. The slot in the shaft without the flat indicates the switch setting in use. Desired wattage or impedance can be obtained by referring to the following table:

GVSP-15T

Switch Position	100V Watts	70V Watts	25V Watts	Ohms
1	2.0	1.0	.12	5000
2	4.0	2.0	.25	2500
3	7.7	3.8	.48	1300
4	15.0	7.5	.94	666
5	*	15.0	1.8	333
6	*	*	7.5	89
7	*	*	15.0	45

* = Do Not Use This Tap On Respective Volts

Ordering information:
GVSP-15T

Public Warning Products

HSS Engineering ApS
Bredskiftevej12
DK-8210
Aarhus, Denmark

Telephone : + 45 7022 8844
Telefax : + 45 7022 8866
URL : www.hss.dk
e-mail : hss@hss.dk