

## All Hazards Rotating Warning Siren

Whelen's VORTEXR1 Series All Hazard High Power Sirens provide an economical alternative for powerful siren communication without compromising quality.

### SYSTEM FEATURES

- VORTEXR1 - Speaker with One Speaker Cell Active
- Two Compartment (Type I) Natural Finish Aluminum Cabinet
- 120dBC @ 100'
- VORTEXR1 Speaker Includes One High Efficiency 400 Watt Speaker Driver
- 15 m cable Included
- Battery Powered, Minimum of 15 Minutes of Full Power Output with Batteries of our Recommendation
- AC Temperature Compensated 5 Amp Battery Charger
- Local Controls or Remote Controls
- One Tone-Only Power Amplifier
- Gear Driven Rotor
- Electronic Siren Controller
- Tone Generator
- Timer
- Local Control Push Buttons
- Rotor Relay Control
- SI TEST®
- Battery Tray
- Lightning Arrestor
- Six Standard Public Warning Tones - Wail, Whoop, Attack, Hi-Lo, Alert, Airhorn

### SYSTEM OPTIONS

- VSBC80 - Solar Power ❶
- Alternate Tone Set

#### NOTES:

- ❶ Solar power option. 2 - 80 watt panels and regulator.

### SIREN ACTIVATION CONTROLS

Our VHF High and UHF siren activation control packages include the following:

- Radio
- Radio Interface
- Tone Squelch
- 2-3dB Gain Omni-Directional Antenna with bracket
- 15 m of RG213 Antenna Cable
- Polyphaser
- SI TEST®

Other features are dependant upon one or two-way controls. Whelen equipment can be interfaced with many different types of two-way radio communications products and systems including 800Mhz trunking, Motorola's MOSCAD, FSK, narrow-band and VHF low band. The



VORTEXR1 cell speaker housing mounted on rotor.

following is available as standard options. Contact factory for special applications.

#### ONE WAY CONTROLS

- VAUXIN - Auxiliary Board for Contact Closure Activation
- VD2020LL - 10 Digit DTMF Landline Activation
- VD2020H - 10 Digit DTMF VHF High Band / 150-170 Mhz
- VD2020U - 10 Digit DTMF UHF / 450-470 Mhz
- VORTT - Two-Tone Sequential Option

#### TWO-WAY CONTROLS

- VAUXCS - Two-Way Contact Closure Activation and Status Board
- VC2020LL - Two-Way Landline Activation
- VC2020H - 10 Digit DTMF VHF High Band / 150-170 Mhz
- VC2020U - 10 Digit DTMF UHF / 450-470 Mhz
- VC2020NH - 10 Digit DTMF VHF High Band narrow-band
- VC2020NU - 10 Digit DTMF UHF Narrow-Band

#### Options:

- VFSKXMOD - Converts the Siren Activation Controls to FSK Format
- VSTATUS - Cabinet Window LED Status Indicator
- VPGINT - Paging Interface to Interface Whelen Tones with Existing Paging Systems



TYPE I ELECTRONIC CABINET (with service door open shows control panel and battery tray with optional batteries).

# VORTEXR1

## Specification Data

Component	Height CM (Inches)	Width CM (Inches)	Depth CM (Inches)	Weight KG (Lbs.)
VORTEXR1 Speaker & Rotor	124.5 (49.0)	72.4 (28.5)	142.2 (56.0)	52.6 (116)
Electronics Cabinet - Type I	82.6 (32.5)	57.2 (22.5)	26.7 (10.5)	22.2 (49)*

\*Less batteries. Two batteries, CTV-80A 2-12V, 80AH Sealed Lead Calcium (user supplied, add 23,3kg)

**WHELEN**<sup>®</sup>  
ENGINEERING COMPANY, INC.  
PUBLIC WARNING PRODUCTS

**hss Engineering**  
Bredskiftevej 12  
DK 8210 Aarhus V  
Phone + 45 70 22 88 44  
Fax + 45 70 22 88 66  
www.hss.dk  
email hss@hss.dk

Whelen Engineering Company, Inc.  
reserves the right to upgrade its products with design  
improvements without notification.  
© 2006 Whelen Engineering Company, Inc.  
Printed in the U.S.A.  
011206-11696B

### ELECTRICAL

- **Battery charger input:** 120VAC, 60Hz, 7A fuse or 240 VAC 50Hz 5A fuse
  - **Battery charger output:** 28VDC, 5A #
  - **Batteries:** 2-12V, 80AH sealed lead calcium (user supplied)
  - **Standby current:** 40mA
  - **Rotor motor:** <1A, 24VDC
  - **Operating current:** 22A, 24VDC
  - **Power amplifier output power:** 400 watts
- #UL recognized component

### ENVIRONMENTAL

- **Operating temperature:** -35C to +60C
- **Storage temperature:** -65C to +125C
- **Humidity, non condensing:** 0 to 95%

### ORDERING INFORMATION

BASIC SYSTEM INCLUDES ALL OF THE FOLLOWING:

- **VORTEXR1** - Speaker assembly & electronics cabinet
- OPTIONS:
- **VAUXIN** - Auxiliary board for contact closure activation
  - **VAUXCS** - Auxiliary / status control board for contact closure activation and status
  - **VD2020LL - VD2020H, VD2020U** - One-way radio control<sup>①</sup>
  - **VC2020LL, VC2020H, VC2020U** - Two-way radio control / status monitoring, COMM/STAT™<sup>①</sup>
  - **VC2020NH, VC2020NU** - Two-way narrow-band radio control / status monitoring, COMM/STAT™<sup>②</sup>
  - **VORTT** - Two-tone sequential
  - **VFSKXMOD** - FSK format
  - **VSTATUS** - Cabinet window LED status indicator
  - **VPGINT** - Paging interface to interface Whelen tones with existing paging systems
  - **VINTRU** - Intrusion alarm
  - **VSBC80** - Solar power<sup>②</sup>
  - **VTXKIT** - Upgrade kit to upgrade VORTEXR1 into a VORTEXR2; 2ea VTXKIT would upgrade to VORTEXR3; 3ea VTXKIT would upgrade to a VORTEXR4
  - **BSETVOR** - One pair of batteries

#### NOTES

① 10 digit DTMF Controls • Landline • VHF High Band / 150-170 Mhz • UHF / 450-470 Mhz  
Our VHF High and UHF siren activation control packages include tone squelch, radio, radio interface, 2-3dB gain omni-directional antenna with bracket, 15 m of RG213 antenna cable and polyphaser.

② Solar power option includes 2 - 80 watt panels, mounting bracket and regulator

③ Contact Factory

### Acoustic Performance

SPL @ 100': 120dB

Estimated 70dB range: 3,200'

Estimated 60dB range: 6,400'

Note: 100' performance levels listed represent repeatable results within +/-2dB to stated levels.  
Estimated 70dB perimeter is based on the Federal Emergency Management Agency's (FEMA) -10dB per distance doubled path model.

